



Sediment and coconut shell carbon

1/4", 3/8" Female NPT and quick connections

Superior spring design to minimize channeling

HYDRONIX ICF/ISF FILTER

utilize NSF listed coconut shell GAC and are designed to remove unpleasant taste and odor and reduce sediment to produce cleaner, clearer, better tasting water. Hydronix ICF Series Granular Activated Carbon Filters are easily installed on the water line to an automatic ice maker, Reverse Osmosis System or water dispensing system.



ICF/ISF SERIES

Inline Filters



ICF-10



ISF-10

Chlorine Taste & Odor Reduction

Coconut Shell Carbon

Service Life	1 yr or 2000 gal (7570 L)
Maximum Flow	.50 GPM (1.9 LPM)
Maximum Pressure	125 PSI (8.6 BAR)
Maximum Temperature	100°F (38°C)
Minimum Temperature	35°F (2°C)

Materials of Construction

Shell:	Polypropylene
Media:	Coconut Shell Carbon
Inner Pads:	Polypropylene

Dirt & Sand Reduction

Service Life:	Applications vary
Maximum Flow:	.50 GPM (1.9 GPM)
Maximum Pressure:	125 PSI (8.6 BAR)
Maximum Temp:	100°F (38°C)
Minimum Temp:	35°F (2°C)
Micron Rating:	5M

Materials of Construction

Shell:	Polypropylene
Media:	Polypropylene

2" DIAMETER SPECIFICATIONS

Part Number	Description
ICF-6	Inline Coconut Filter: 1,000 Gallon, 2" x 6", 1/4" FNPT
ICF-6Q	Inline Coconut Filter: 1,000 Gallon, 2" x 6", 1/4" Hydrofit™ QC
ICF-6Q38	Inline Coconut Filter: 1,000 Gallon, 2" x 6", 3/8" Hydrofit™ QC
ICF-10	Inline Coconut Filter: 2,000 Gallon, 2" x 10", 1/4" FNPT
ICF-10Q	Inline Coconut Filter: 2,000 Gallon, 2" x 10", 1/4" Hydrofit™ QC
ICF-10Q38	Inline Coconut Filter: 2,000 Gallon, 2" x 10", 3/8" Hydrofit™ QC
ISF-10	Inline Sediment Filter: 2" x 10", 1/4" FNPT

2.5" DIAMETER SPECIFICATIONS

Part Number	Description
ICF-2512	Inline Coconut Filter: 3,500 Gallon, 2.5" x 12", 1/4" FNPT
ICF-2512Q	Inline Coconut Filter: 3,500 Gallon, 2.5" x 12", 1/4" Hydrofit™ QC
ISF-2512	Inline Sediment Filter: 2.5" x 12", 1/4" FNPT
ISF-2512Q	Inline Sediment Filter: 2.5" x 12", 1/4" Hydrofit™ QC

ALKALINE/ORP FILTER - 2.5" DIAMETER SPECIFICATIONS

Part Number	Description
ALK ICF-2512-ALK	Inline Alkaline/ORP Filter: 2,000 GAL, 2.5" X 12", 1/4" FNPT

Available Port Sizes

- 1/4" Female NPT Basic
- 3/8" Female NPT Basic
- 1/4" Quick Connect
- 3/8" Quick Connect

Applications

- Ice makers
- Reverse osmosis systems
- Water Coolers
- Coffee makers
- Refrigerators

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

LIT-ICF-SS 05/03/16

Distributed by:

HYDRONIX WATER TECHNOLOGY

P.O. Box 2235 Chino Hills, CA 91709 | USA

sales@hydronixwater.com • www.HydronixWater.com