

ICF/ISF Series Inline Filters

- ✓ Superior spring design to minimize channeling
- ✓ 1/4", 3/8" Female NPT and quick connections
- ✓ Sediment and coconut shell carbon



HYDRONIX ICF/ISF FILTER

utilize NSF listed coconut shell GAC and are designed to remove unpleasant taste and odor and reduce sediment to produce cleaner, clearer, better tasting water. Hydronix ICF Series Granular Activated Carbon Filters are easily installed on the water line to an automatic ice maker, Reverse Osmosis System or water dispensing system.



Tested and certified by NSF International to ANSI/NSF Standard 42 for material requirements only.

* For the complete list of our NSF Certified products, please visit the Hydronix Water Technology page on the official NSF website: www.nsf.org/certified-products-systems

2" DIAMETER SPECIFICATIONS						
	Part Number	Description	Case Quantity	Box Dimension (Inches)	Weight (lbs)	Weight (kgs)
6"	ICF-6	NSF Inline Coconut Filter: 1,000 Gallon, 2" x 6", 1/4" FNPT	50	12.5 x 11 x 11	18	8.16
	ICF-6Q	Inline Coconut Filter: 1,000 Gallon, 2" x 6", 1/4" Hydrofit™ QC	50	12.5 x 11 x 11	18	8.16
	ICF-6Q38	Inline Coconut Filter: 1,000 Gallon, 2" x 6", 3/8" Hydrofit™ QC	50	12.5 x 11 x 11	18	8.16
10"	ICF-10	NSF Inline Coconut Filter: 2,000 Gallon, 2" x 10", 1/4" FNPT	25	10.5 x 10.5 x 11	17	7.71
	ICF-10Q	Inline Coconut Filter: 2,000 Gallon, 2" x 10", 1/4" Hydrofit™ QC	25	11.5 x 10.5 x 10.5	17	7.71
	ICF-10Q38	Inline Coconut Filter: 2,000 Gallon, 2" x 10", 3/8" Hydrofit™ QC	25	10.5 x 11 x 11	17	7.71
	ISF-10	Inline Sediment Filter: 2" x 10", 1/4" FNPT	25	10.5 x 10.5 x 11	12	5.44
	ISF-10Q	Inline Sediment Filter: 2" x 10", 1/4" FNPT Hydrofit™ QC	25	11.5 x 10.5 x 10.5	12	5.44

2.5" DIAMETER SPECIFICATIONS						
	Part Number	Description	Case Quantity	Box Dimension (Inches)	Weight (lbs)	Weight (kgs)
12"	ICF-2512	NSF Inline Coconut Filter: 3,500 Gallon, 2.5" x 12", 1/4" FNPT	25	13.25 x 11.75 x 13.5	26	11.79
	ICF-2512Q	Inline Coconut Filter: 3,500 Gallon, 2.5" x 12", 1/4" Hydrofit™ QC	25	13 x 12.5 x 13.5	27	12.25
	ISF-2512	Inline Sediment Filter: 2.5" x 12", 1/4" FNPT	25	13.25 x 11.75 x 13.5	19	8.62
	ISF-2512Q	Inline Sediment Filter: 2.5" x 12", 1/4" Hydrofit™ QC	25	13.25 x 12.25 x 13.5	20	9.07

Available Port Sizes: 1/4" Female NPT Basic; 1/4" Hydrofit™ Quick Connect; and 3/8" Hydrofit™ Quick Connect.

*WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



ICF/ISF SERIES

Inline Filters
Data Sheet



ICF-10



ISF-10

Chlorine Taste & Odor Reduction - ICF-10 | ICF-10Q | ICF-10Q38

Coconut Shell Carbon	
Service Life	1 yr or 2000 gal (7570 L)
Maximum Flow	.50 gpm (1.9 lpm)
Maximum Pressure	125 psi (8.6 bar)
Maximum Temperature	100 °F (38 °C)
Minimum Temperature	35 °F (2 °C)

Materials of Construction


Shell:	Polypropylene
Media:	Coconut Shell Carbon
Inner Pads:	Polypropylene

Available Port Sizes

- 1/4" Female NPT Basic
- 3/8" Female NPT Basic
- 1/4" Quick Connect
- 3/8" Quick Connect

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Distributed by:



Dirt & Sand Reduction - ISF-10 | ISF-10Q

Service Life:	Applications vary
Maximum Flow:	.50 gpm (1.9 lpm)
Maximum Pressure:	125 psi (8.6 bar)
Maximum Temp:	100 °F (38 °C)
Minimum Temp:	35 °F (2 °C)
Micron Rating:	5M

Materials of Construction

Shell:	Polypropylene
Media:	Polypropylene

Applications

- Ice makers
- Reverse osmosis systems
- Water Coolers
- Coffee makers
- Refrigerators



JUST ADD WATER™

P.O. Box 2235 Chino Hills, CA 91709 | USA
sales@hydronixwater.com • www.HydronixWater.com