



# PMP-300GPD

## BOOSTER PUMP



### PMP-300GPD SPECIFICATIONS


<b>MODEL NUMBER:</b>	PMP-300GPD
<b>PUMP DESIGN:</b>	Positive displacement
<b>Diaphragm pump:</b>	Three Chamber
<b>MOTOR:</b>	Permanent magnet
<b>VOLTAGE:</b>	36VDC
<b>PRESSURE SWITCH:</b>	NONE
<b>LIQUID TEMPERATURE:</b>	140 °F (60 °C) max.
<b>PRIME:</b>	Self-priming up to 2 meter
<b>RUNS DRY:</b>	WITHOUT DAMAGE
<b>PORTS:</b>	3/8" - 18 NPT female
<b>NET WEIGHT:</b>	4.65 lbs (2.11 kg)
<b>WETTED PARTS:</b>	FDA food grade material
<b>TYPICAL APPLICATIONS:</b>	R.O. booster pump and water delivery

NOTE: RECOMMENDED SHUT OFF TEMPERATURE: 150 °F. (REQUIRED TO SHUT DOWN WHILE THE MOTOR COOLS DOWN.)

INLET - 15 PSI		
PRESSURE (PSI)	FLOW GPM /(L/min)	CURRENT (AMPS)
20	1.16 / 4.40	0.86
30	1.13 / 4.28	1.06
40	1.09 / 4.13	1.24
50	1.05 / 3.98	1.40
60	1.02 / 3.85	1.58
70	0.97 / 3.70	1.76
80	0.95 / 3.60	1.99
90	0.92 / 3.50	2.11
100	0.86 / 3.27	2.26

*All data based on testing with water  
Voltage (Volts): 36 VDC/1.5A/Adaptor*

NOTE: Performance will vary with variation in service voltage and transformer output



LIT-PMP-300GPD-DS 10/15/18



AQUATROL | P.O. Box 2235 Chino Hills, CA 91709 • USA

Distributed by:

[WWW.AQUATROLTECH.COM](http://WWW.AQUATROLTECH.COM)