

HPL-LED Series

Pool Lighting

- ✓ Waterproof Standard: IP68
- ✓ Low Power Consumption
- ✓ ABS + UV Stabilizer
- ✓ State of the art LED Technology
- √ 40,000 Lamp Hours
- ✓ Intense Light and Angle Illumination
- ✓ White, Warm White, RGB LED
- ✓ Auto Synchronization



HYDRONIX POOL HPL-LED SERIES

Incorporate five highly luminous LED colors: Cool White, Warm White, Red-Green-Blue (RGB), they are high power and constant color rendering and are equipped with state-of-the-art LED technology, HPL-LED ensures increased energy and luminous efficacy achieving 80 lumens per watt. LED life exceeds 40,000 hours.

The innovative design of the diffusion lens and bulb matrix provides exceptional reflection, brightness and throw of angle of illumination. The perforations on the face ring contribute to the light intensity and angle of illumination by allowing light penetration throughout. Self determined operation mode with or without Color Touch controller. Automatic color synchronization among lights and zones.



CE Solis IP68

HPL-LED SERIES SPECIFICATIONS					
Part Number	Voltage	Max Power	Color	Illuminance (lux)	Face Ring
HPL-LED-WHRGB	12-32V AC 50/60Hz	25W	White, Warm White, RGB Multi Color	325-350	White



HPL-LED SERIES

Pool Lighting Data Sheet

Standard Features

- Ultra-Thin, Low Power Consumption Light
- Resin Filled LED Panel
- 2.5 Meter Cable
- Unique Face Ring Preforations
- Warm White, White, RGB Color LED
- ABS Construction
- IPS68 Waterproof


Materials of Construction

Housing: Durable ABS structure


LED Lamp Life: 40K Hours

Max Temp: 0°-77° F (0° - 25° C)

Dimensions in (mm)



Illumination Distance



Angle and distance of illumination

Distributed by:





JUST ADD WATER™

P.O. Box 2235 Chino Hills, CA 91709 | USA sales@hydronixwater.com • www.HydronixWater.com